

## Flexible firestop sealant CP 606



### Applications

- Sealing rigid or low-movement ceiling/wall joints, widths from 6 to 30 mm
- Sealing cable tray penetrations
- Sealing metal pipe penetrations
- For use in various base materials such as masonry, concrete, drywall and metal

### Advantages

- Paintable
- Good adherence without primer
- Easy clean up with water
- Smoke, fume and water resistant
- Tested for 500 cycles with up to 33% movement in accordance with UL 2079 and ASTM E1966
- Meets LEED™ requirements for indoor environmental quality credit 4.1 Low Emitting Materials, Sealants and Adhesives and 4.2 Paints and Coatings

### Technical data

<b>Chemical basis</b>	Water-based acrylic dispersion
<b>Base materials</b>	Concrete, Masonry, Drywall, Steel
<b>Tested in accordance with</b>	UL 2079, ASTM E814, ASTM E1966, UL 1479, CAN/ULC-S115
<b>Movement<sup>1)</sup></b>	±12.5% (ISO 11600)
<b>LEED VOC</b>	75 g/l
<b>Can be painted</b>	Yes
<b>Approx. curing time<sup>2)</sup></b>	3 mm/3 days
<b>Intumescent</b>	No
<b>Application temperature range</b>	5 - 40 °C
<b>Storage and transportation temperature range</b>	5 - 25 °C
<b>Temperature resistance range</b>	-30 - 80 °C
<b>Colour</b>	White / Grey

<sup>1)</sup> according to HTC 1250

<sup>2)</sup> at 75°F/24°C, 50% relative humidity



**British Standard**  
BS 476-20



Ordering designation	Volume per unit	Packaging	Sales pack quantity	Item number
CP 606 310ml INT grey	310 ml	Cartridge	1	209630
CP 606 310ml white	310 ml	Cartridge	1	209625